


















ARTEL

**NIEUW IN HET
ASSORTIMENT**



Moederhaard Corridor



Artel Corridor		16 kW		20 kW		24 kW	
	Eenheid	Max.	Min.	Max.	Min.	Max.	Min.
 POWER Vermogen	kW	16.2	4,12	20	5,5	24	5,51
 POWER Verm. water	kW	15	4.0	18,4	4.9	22,14	4.95
 Rendement	%	97.1	92	90,1	89,3	90,1	89
 Rookgas Temp.	°C	130	63	135	63	140	63
 Min. afv. druk	Pa	12	12	12	12	12	12
 Afvoer Diam.	mm	Ø 80		Ø 80		Ø 80	
 Inlaat Diam.	mm	Ø 50		Ø 50		Ø 50	
 CV aansluiting	Inch	3/4		3/4		3/4	
 Ketel Liter inh.	l	80		80		80	
 Pellettank Inh.	kg	19		19		19	
 Pellet diameter	mm	Ø 6		Ø 6		Ø 6	
 Verbruik / uur	kg/h	2,95	0,9	3,6	1,1	4,4	1,1
 Branduren/tank	h	15	50	16,6	54	13,6	54,5
 Oppervlakte	m ³	* 350		* 400		* 500	
 Gewicht	kg	160		205		215	
Afmeting	HxBxD	1000x1100x 249		1000x1100x 249		1000x1100x 249	

* Verwarmbaar volume is gebaseerd op een redelijk tot goed geïsoleerde woning met standaard hoogte van 270 cm.